

	564	574
CAT® Engine	C6.6 ACERT	C6.6 ACERT
Gross Power	129 kW (173 HP)	129 kW (173 HP)
Standard Wood Bunk Length	4.88m (16')	4.88m (16')
- Optional	5.64m (18.5')	5.64m (18.5')
Operating Weight	16,330 kg (36,000 lb)	17,237 kg (38,000 lb)

Caterpillar® Forwarders



Structures

- Large engine side covers
- Heavy-duty engine and radiator house
- Purpose-built blade with wear resistant front cutting edge
- Optional brush sweeps
- Heavy frame articulation points

Loader Features

- Rear mounted loader with durable rack and pinion swing system
- Wrapped hoses
- Full load high reach boom
- 250° rotation
- European style butt-bypass grapple with high strength steel dampener

Caterpillar forwarders have proven, over-sized components including heavy-duty axles and torque converter power shift transmission. The spacious, comfortable operator station is designed for exceptional visibility.




Forwarder General Specifications

ALD .
Axle Front
Axle Rear
Front Axle Bogie lift
Engine
Standard Engine kw
Standard Engine hp
Fuel
Standard Tire Front
Standard Tire Rear
Optional Tire Front (other sizes available on request)
Optional Tire Rear (other sizes available on request)
Transmission
Gears
Maximum Forward Speed
Variable displacement load sensing piston pump
Flow @ 2200 rpm
Reservoir Capacity
Loader with Telescopic Boom - 6.93m (22 ft, 9 in) Reach
8.53 m (28 Sq ft) Clam Bunk
Bogie Tracks
Standard Operating Weight
Load Capacity
Load Capacity with Clam Bunk Attachment

564, 6-Wheel
Funk 1200
NAF Bogie (HD)
CAT C6.6 ACERT
129
173
178 L (47 gal)
28 L x 26
700/50 x 26.5
30.5 x 32
800/50 x 26.5
Electric Power Shift
4/4
23.33 km/h (14.5 mph)
PVG 100 cc
250 l/m (66 gpm)
121 L (32 gal)
Standard
Optional
Optional
16,330 kg (36,000 lbs)
13,608 kg (30,000 lbs)
11,793 kg (26,000 lbs)

574, 8-Wheel
NAF Bogie (HD)
NAF Bogie (HD)
Optional
CAT C6.6 ACERT
129
173
178 L (47 gal)
700/50 x 26.5
700/50 x 26.5
800/50 x 26.5
800/50 x 26.5
Electric Power Shift
4/4
23.33 km/h (14.5 mph)
PVG 100 cc
250 l/m (66 gpm)
121 L (32 gal)
Standard
Optional
Optional
17,237 kg (38,000 lbs)
14,525 kg (32,000 lbs)
11,793 kg (26,000 lbs)

Forwarder Basic Dimensions



Length (With Blade Raised)
4.88 m (16 ft) Bunk
5.64m (18.5 ft) Bunk
Ground Clearance
Width with Standard Tires
Transport Height
Wheel Base
4.88 m (16 ft) Bunk
5.64m (18.5 ft) Bunk
Load Stake Width (Inside)
Length of Wood Bunk
Optional Length

564, 6-Wheel
10.21 m (402 in)
10.97 m (432 in)
579 mm (22.8 in)
2997 mm (118 in)
3581 mm (141 in)
, ,
5334 mm (210 in)
5715 mm (225 in)
2591 mm (102 in)
4.88 m (16 ft)
5.64m (18.5 ft)

574, 8-Wheel
<u></u>
10.21 m (402 in)
10.97 m (432 in)
579 mm (22.8 in)
3048 mm (120 in)
3581 mm (141 in)
5334 mm (210 in)
5715 mm (225 in)
2591 mm (102 in)
4.88 m (16 ft)
5.64 m (18.5 ft)

Cat, CATERPILLAR their respective logos ACERT and "Caterpillar Yellow", as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

For more complete information on CAT products, dealer services, and industry solutions, visit us on the web at www.cat.com and www.forestpro.com

©2007 All Rights Reserved Printed in the USA Order Form # CATFWD-2(08-07)

