

Cat® Waste Handling Buckets

950-980 Wheel Loaders

Waste Handling Buckets are available with pin-on interface or for use with the Fusion™ Coupler System. Bolt-on cutting edge included.

Contact your Cat® dealer for more information.

Fusion™

	Width (Bare)		Capacity		Bucket Weight (Bare)	
	mm	(in)	m^3	(yd^3)	kg	(lb)
950H 962H	3,059	(120)	5.20	(6.75)	2,197	(4,844)
950K	3,059	(120)	5.20	(6.75)	2,115	(4,663)
962K	3,059	(120)	6.10	(8.00)	2,285	(5,038)
IT62G / IT62H	3,059	(120)	5.20	(6.75)	2,073	(4,570)
966H / 966K 972H/ 972K	3,323	(131)	6.50	(8.50)	2,569	(5,664)

Pin-on

	Width (Bare)		Capacity		Bucket Weight (Bare)	
	mm	(in)	m^3	(yd^3)	kg	(lb)
950H 962H	3,059	(120)	5.20	(6.75)	2,541	(5,602)
950K	3,059	(120)	5.20	(6.75)	2,250	(4,960)
962K	3,059	(120)	6.10	(8.00)	2,425	(5,346)
966H / 966K 972H/ 972K	3,357	(132)	6.50	(8.50)	2,925	(6,449)
980H / 980K	3,886	(153)	9.80	(12.75)	3,908	(8,615)





Cat Waste Handling Buckets

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at **www.cat.com**

GEHQ0024 (02-14)

©2014 Caterpillar All Rights Reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," and the POWER EDGE trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

